

	HIVIDEO
SPECIFICATION	<ul> <li>Adopting T23 main control, dual 1920 * 1080P (2MP) high-definition images, H264 encoding, clear and delicate day and night images;</li> <li>Dual lens dual screen viewing, monitoring different perspectives separately, bidding farewell to blind spots in surveillance;</li> <li>The gun ball stereo camera is used for collaborative monitoring, with a small focal length lens for the gun mechanism, allowing for wide range monitoring, and a large focal length lens for the ball mechanism,</li> <li>Used for capturing local details and tracking targets;</li> <li>Support Bluetooth distribution network function, greatly improving the success rate of device</li> </ul>
	distribution network; <ul> <li>Support dual infrared lights;</li> <li>Support immediate sleep and scheduled sleep functions to protect user privacy;</li> <li>Support humanoid tracking function;</li> <li>Support TF card recording, TF card supports up to 256GB;</li> <li>Support centralized management of NVR and HIVIDEOVMS clients;</li> <li>Support full duplex voice calls;</li> <li>Support ONVIF protocol</li> </ul>
Camera SPEC	1

## **Camera SPEC**

Image Sensor	Dual 1/3.2 CMOS Sensor for high-definition	
Resolution	2MP	
Effective Pixels	1920*1080P	
Compression	Н.264	
TV System	PAL/NTSC	
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec	
Usable Illumination	Day mode 1Lux, night vision mode 0.01Lux	
S/N Ratio	≥52dB	
Video Output	HIVIDEO VMS/HIVIDEO APP	
Reset Button	Support	
NVR	Support(Paired with 810A/816A/910A/916A/936A, manually add image)	
Network		
WIFI	WIFI 2.4G	

BLE	Supports Bluetooth network configuration function	
Р2Р	Support	
Audio	Support	
Video Delay	0.3S (Within the Lan)	
Smart Phone	iPhone, iPad, Android, Android Pad	
Frames Per Second	10Fps	
Camera Features		
Day/Night	full Color / B&W	
Image Config	Saturation/Brightness/Contrast /Sharpness,Mirror, 3D NR , White Balance, BLC, FLK(FlickerControl)	
Motion Detection	Support humanoid automatic tracking, two way Audio,Built-in loudspeaker warning,Speaker alarm can record its own sound;	
Sleep function	Support	
Recording Mode	NVR/APP/VMS	
TF card capacity	Maximum support of 256GB (general-purpose FAT 32 format)	
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German,Russian, French,Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian	
Audio	G.711	
LENS Type		
Lens Type	Fixed	
Lens	Top Camera 6mm Lens/Bottom Camera 2.8mm Lens	
Night Vision		
Infrared LED	Top Camera 4PCS Smart Dual Light LED/Bottom Camera 8PCS Smart Dual Light LED	
Infrared Distance	25-30M	
IR Status	Under 10 Lux	
IR Power On	Sensor Auto Control	
General		
Housing	Plastic , IP66	
Bracket	YES	
IR Cut Filter	YES	
Operation Temperature	-20℃ ~ +55℃ RH95% Max	
Storage Temperature	-20℃ ~ +55℃ RH95% Max	
Power Source	DC: 5V	
Working current	530mA ±10mA	
Dimension	Size: 79(W) x79(H) x 121(D)mm	
Weight	Weight: 0.2Kg	