

Safety Data Sheet according to GB/T 16483-2008

Page 1 of 6.

SDS No.: 44195

V001.6 Revision: 27.10.2021

printing date: 26.03.2022

TECHNOMELT PA 652 N BG20KG

1. Identification of the substance/preparation and of the company/undertaking

TECHNOMELT PA 652 N BG20KG **Product name:**

Intended use: Special hotmelt, based on polyamide

Manufacturer/Importer/Distributor Representative Company

Henkel Adhesive Technology (Shanghai) Co., Ltd. Room 105, 2B (Building 1), No. 928 Zhangheng Road, China (Shanghai) Pilot Free Trade Zone 201204 Pudong New Area, Shanghai, P.R. China

China

Phone: +86-21-2891 8000 +86-21-2891 5137 Fax-no.:

E-mail: ap-ua-psra.china@henkel.com

Revision date: 27.10.2021

Emergency information: +86 21 2891 8311 (24h).

2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 (General rule for classification and hazard communication of chemicals):

No classification required.

Label elements according to GB 15258-2009 (General rules for preparation of precautionary label for chemicals):

No classification required.

3. Composition / information on ingredients

General description: Mixture

Declaration of the ingredients according to GB 13690-2009:

Hazard component CAS-No.	Content	GHS Classification
Bis(4-(1,1,3,3-tetramethylbutyl)phenyl)amine	1- < 2.5 %	Chronic hazards to the aquatic environment 4
15721-78-5		H413

Only hazardous ingredients for which a classification according to GB 13690-2009 is already available are displayed in this table. For full text of the Hazard statements see section 16 "Other information".

SDS No.: 44195 TECHNOMELT PA 652 N BG20KG

V001.6

4. First aid measures

Skin contact: Molten adhesive may cause severe burns.

Eye contact: After contact with the hot melt: cool with water, seek medical attention.

Inhalation: Move to fresh air, consult doctor if complaint persists.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

5. Fire fighting measures

Hazardous combustion products: carbon oxides.

Extinguishing media: All common extinguishing agents are suitable.

Notice and measures for firing

fighting:

In case of fire toxic gases can be released.

Wear protective equipment.

Wear self-contained breathing apparatus.

6. Accidental release measures

Emergency measures: Wear protective equipment.

Do not empty into drains / surface water / ground water.

Clean-up methods: Remove mechanically.

7. Handling and storage

Notice for handling: Wash thoroughly after handling.

Avoid generating static electricity while handling. Use proper grounding procedures when

handling near flammable or explosive materials.

Use only with adequate ventilation.

Do not taste or swallow.

Avoid contact with eyes, skin and clothing.

Notice for storage: Store in sealed original container.

Refer to Technical Data Sheet

8. Exposure controls / personal protection

Hazardous components	GBZ 2.1-2019	ACGIH	NIOSH	OSHA
Bis(4-(1,1,3,3-	none	none		none
tetramethylbutyl)phenyl)amine				

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Suitable breathing mask when there is inadequate ventilation.

Eye protection: Protective goggles

Body protection: Wear protective equipment.

SDS No.: 44195

V001.6

TECHNOMELT PA 652 N BG20KG

Hand protection: Wear heat resistance gloves while working with the hot melt (EN 407).

Other protection: Use only personal protection that's CE-labelled according to Directive 89/686/EEC

(Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

Pictograms for recommended PPE:



9. Physical and chemical properties

Physical state: solid Appearance: Amber typical Not available. Odor: Evaporation rate: Not available. Melting point: Not available. pH: Boiling point: Not available. Density: Not available. Not available. Not available. Vapor density: Vapor pressure: Flash point: Not applicable Ignition temperature: Not available. Lower explosive limit: Not available. Upper explosive limit: Not available. Solubility in water Not available. Viscosity: Not available.

Auto-ignition temperature: Not available. Flammability: Not available. Octanol / water distribution Not available. Decomposition temperature: Not available.

coefficient:

VOC: Bulk adhesive

Thermoplastic

Transportation, Assembly Industry

< 50 g/kg, GB 33372-2020 Limit of volatile organic compounds content in adhesive

10. Stability and reactivity

Stability: Stable under recommended storage conditions.

Conditions to avoid: None if used for intended purpose. **Incompatible products:** None if used for intended purpose.

Decomposition products: No decomposition if used according to specifications.

11. Toxicological information

General toxicological information:

No laboratory animal data available.

SDS No.: 44195 V001.6

TECHNOMELT PA 652 N BG20KG

Carcinogenicity

No data available.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Bis(4-(1,1,3,3-	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 423 (Acute
tetramethylbutyl)phenyl)a	LD50	> 2,000 mg/kg			rat	Oral toxicity)
mine			dermal			OECD Guideline 402 (Acute
15721-78-5						Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
	not irritating	4 h	rabbit	OECD Guideline 404 (Acute
tetramethylbutyl)phenyl)a				Dermal Irritation / Corrosion)
mine				
15721-78-5				

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Bis(4-(1,1,3,3- tetramethylbutyl)phenyl)a	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
mine 15721-78-5				

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Bis(4-(1,1,3,3- tetramethylbutyl)phenyl)a	not sensitising	Patch-Te	t human	Human volunteer study
mine				
15721-78-5				

Germ cell mutagenicity:

Hazardous components	Result	Type of study/	Metabolic	Species	Method
CAS-No.		Route of	activation/		
		administration	Exposure time		
Bis(4-(1,1,3,3-	negative	bacterial reverse	with and without		OECD Guideline 471
tetramethylbutyl)phenyl)a	ambiguous	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
mine	with metabolic	Ames test)	with and without		Assay)
15721-78-5	activation	mammalian cell			OECD Guideline 476 (In vitro
	negative	gene mutation assay			Mammalian Cell Gene
		in vitro mammalian			Mutation Test)
		chromosome			OECD Guideline 473 (In vitro
		aberrationtest			Mammalian Chromosome
					Aberration Test)

12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

SDS No.: 44195 V001.6

TECHNOMELT PA 652 N BG20KG

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
D: (1 (1 1 2 2	Y 050	777	Study	0.51		orgo a : i i:
Bis(4-(1,1,3,3-	LC50	Toxicity > Water	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
tetramethylbutyl)phenyl)amin		solubility				203 (Fish, Acute
e						Toxicity Test)
15721-78-5						
Bis(4-(1,1,3,3-	EC50	Toxicity > Water	Daphnia	48 h	Daphnia magna	OECD Guideline
tetramethylbutyl)phenyl)amin		solubility				202 (Daphnia sp.
e						Acute
15721-78-5						Immobilisation
						Test)
Bis(4-(1,1,3,3-	EC50	Toxicity > Water	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline
tetramethylbutyl)phenyl)amin		solubility	C		•	201 (Alga, Growth
e		ř				Inhibition Test)
15721-78-5						

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Bis(4-(1,1,3,3- tetramethylbutyl)phenyl)amin e	not readily biodegradable.	aerobic	20 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
15721-78-5				

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Bis(4-(1,1,3,3-	8.8				40 °C	OECD Guideline 117
tetramethylbutyl)phenyl)amin						(Partition Coefficient (n-
е						octanol / water), HPLC
15721-78-5						Method)

13. Disposal considerations

Product disposal: Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

14. Transport information

Road transport CN_DG:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Notice For Transportation:

Transport according to local and national regulations. Ensure containers will not leak, collapse, or being damaged when transported. DO NOT transport with incompatible materials. Transportation vehicle should be equipped with right fire-fighting equipment in case of emergency. Avoid solarization, drenched and high temperature when transported.

SDS No.: 44195

V001.6

TECHNOMELT PA 652 N BG20KG

15. Regulatory information

The following laws and regulations lay down provisions in terms of chemicals safety use, storage, transportation, loading/unloading, classification as well as symbol.

"Law of the People's Republic of China on Work Safety" (Adopted by the 28th meeting of 9th NPC standing committee on 29th June 2002, revised by 10th meeting of 12nd NPC standing committee on 31st Aug 2014).

Law of the People's Republic of China on the Prevention and Treatment of Occupational Diseases" (Adopted by the 24th meeting of 9th NPC standing committee on 27th October 2001, revised by 7th meeting of 13rd NPC standing committee on 29th Dec 2018).

"Law of the People's Republic of China on environmental protection" (Adopted by 11st meeting of 7th NPC standing committee on 26th December 1989, revised by 8th meeting of 12nd NPC standing committee on 24th Apr 2014).

"Regulation on the Safety Management of Hazardous Chemicals" (Adopted by 32nd State Council executive meeting on 4th December 2013).

"Regulations on License to Work Safety" (Adopted by 54th State Council executive meeting on 29th July 2014).

16. Other information

Issue date:

26.03.2022

Issue department:

Product Safety & Regulatory Affairs for China

Disclaimer:

This Safety Data Sheet has been generated in accordance with Chinese law only. It provides information on the chemical product in the aspects of safety, health, environment, etc, recommending preventive and protective measures and countermeasures in case of emergency. The information contained herein does not constitute a guarantee concerning the properties of the material. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties. The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Others:

The full text of all abbreviations indicated by codes in this safety data sheet section 3 are as follows:

H413 May cause long lasting harmful effects to aquatic life.