

Safety Data Sheet according to GB/T 16483-2008

Page 1 of 6.

TECHNOMELT PA 2035 BLACK known as REAMMIDE PAS 5035 S

SDS No.: 120485 V001.6

Revision: 04.11.2020 printing date: 26.03.2022

1. Identification of the substance/preparation and of the company/undertaking

Product name: TECHNOMELT PA 2035 BLACK known as REAMMIDE PAS 5035 S

Trade name: Reammide PAS 5035 S

Manufacturer/Importer/Distributor Representative Company

Henkel Adhesive Technology (Shanghai) Co., Ltd. Room 105, 2B (Building 1), No. 928 Zhangheng Road, China (Shanghai) Pilot Free Trade Zone 201204 Pudong New Area, Shanghai, P.R. China

China

Phone: +86-21-2891 8000 Fax-no.: +86-21-2891 5137

E-mail: ap-ua-psra.china@henkel.com

Revision date: 04.11.2020

Emergency information: Emergency telephone: +86 21 2891 8311 (24h).

2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 (General rule for classification and hazard communication of chemicals):

No classification required.

Label elements according to GB 15258-2009 (General rules for preparation of precautionary label for chemicals):

No classification required.

3. Composition / information on ingredients

General description: Mixture

Declaration of the ingredients according to GB 13690-2009:

Hazard component CAS-No.	Content	GHS Classification
Benzenamine, N-phenyl-, reaction products with 2,4,4-	1- < 2.5 %	Acute hazards to the aquatic environment 3
trimethylpentene		H402
68411-46-1		Chronic hazards to the aquatic environment 3
		H412

Page 2 of 6.

SDS No.: 120485 V001.6

TECHNOMELT PA 2035 BLACK known as REAMMIDE PAS 5035 S

Only hazardous ingredients for which a classification according to GB 13690-2009 is already available are displayed in this table. For full text of the Hazard statements see section 16 "Other information".

4. First aid measures

Skin contact: Molten product. After skin contact cool down immediately with cold water. Do not

remove adherent product. Seek medical advice.

Eye contact: After contact with the hot melt: cool with water, seek medical attention.

Inhalation: Move to fresh air, consult doctor if complaint persists.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

5. Fire fighting measures

Hazardous combustion products: Irritating vapors.

Extinguishing media: All common extinguishing agents are suitable.

Fire-fighting method: In case of fire use foam or powder extinguisher.

Notice and measures for firing

fighting:

In case of fire toxic gases can be released.

Wear protective equipment.

6. Accidental release measures

Emergency measures: Wear protective equipment.

Do not empty into drains / surface water / ground water.

Clean-up methods: Allow to solidify.

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

7. Handling and storage

Notice for handling: Always be careful around molten material.

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash

thoroughly after handling.

Notice for storage: Keep only in original container.

Store in a dry place.

< + 35 °C

Store between 0°C and 32°C. (32°F and 90°F)

8. Exposure controls / personal protection

Hazardous components	GBZ 2.1-2019	ACGIH	NIOSH	OSHA
Paraffin waxes and Hydrocarbon waxes	2 mg/m3PC-TWA Fume. 4 mg/m3PC-STEL Fume.	2 mg/m3 TWA Fume.		none

Engineering controls: Ensure good ventilation/extraction.

SDS No.: 120485

V001.6

TECHNOMELT PA 2035 BLACK known as

REAMMIDE PAS 5035 S

Respiratory protection: Suitable breathing mask when there is inadequate ventilation.

Eye protection: Protective goggles

Body protection: Wear protective equipment.

Hand protection: Wear refractive gloves while working with the hot melt.

Other protection: The selection of PPE shall at least compliant with "Law of the People's Republic of China

on Prevention and Control of Occupational Diseases" and "Code of practice for selection

of personal protective equipments" (GB/T 11651-2008).

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while

black

Not available.

Not available.

working.

Pictograms for recommended PPE:







9. Physical and chemical properties

Physical state: solid Appearance:

Not available.

Not available.

Not available. characteristic Evaporation rate: Odor: Not available. Melting point: Not available. pH: Boiling point: Not available. Not available. Density: Vapor density: Not available. Vapor pressure: Not available. No flash point up to 200 $^{\circ}\mathrm{C}$ Flash point: Ignition temperature: Not applicable Lower explosive limit: Not available. Upper explosive limit: Not available. Solubility in water Not available. Viscosity: 3,000 - 6,500 mPa.s

Auto-ignition temperature: Octanol / water distribution

coefficient:

VOC: Bulk adhesive

Thermoplastic Assembly Industry

< 50 g/kg , GB 33372-2020 Limit of volatile organic compounds content in adhesive

Flammability:

Decomposition temperature:

10. Stability and reactivity

Stability: Stable under normal conditions of storage and use.

Conditions to avoid: None if used for intended purpose. **Incompatible products:** None if used for intended purpose.

Decomposition products: No decomposition if used according to specifications.

Hazardous polymerization: Will not occur.

11. Toxicological information

General toxicological information:

No laboratory animal data available.

SDS No.: 120485 V001.6

TECHNOMELT PA 2035 BLACK known as REAMMIDE PAS 5035 S

Other remarks:

Not available.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Benzenamine, N-phenyl-,	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 401 (Acute
reaction products with	LD50	> 2,000 mg/kg			rat	Oral Toxicity)
2,4,4-trimethylpentene			dermal			equivalent or similar to OECD
68411-46-1						Guideline 402 (Acute Dermal
						Toxicity)

12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Ecotoxicity:

Harmful to aquatic life.

Other adverse effects:

Not available.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Benzenamine, N-phenyl-, reaction products with 2,4,4- trimethylpentene 68411-46-1	LC50	>71 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4- trimethylpentene 68411-46-1	EC50	51 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4- trimethylpentene 68411-46-1	EC50	> 100 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4- trimethylpentene 68411-46-1	NOEC	10 - 100 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Benzenamine, N-phenyl-, reaction products with 2,4,4- trimethylpentene 68411-46-1	IC50	> 100 mg/l	Bacteria	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Benzenamine, N-phenyl-, reaction products with 2,4,4- trimethylpentene 68411-46-1	not readily biodegradable.	aerobic	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.	factor (BCF)	time			

Page 5 of 6.

SDS No.: 120485 V001.6

TECHNOMELT PA 2035 BLACK known as REAMMIDE PAS 5035 S

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene 68411-46-1		>411 - 1,730	42 d	Cyprinus carpio	24 °C	other guideline:
Benzenamine, N-phenyl-, reaction products with 2,4,4- trimethylpentene 68411-46-1	> 5				25 °C	QSAR (Quantitative Structure Activity Relationship)

13. Disposal considerations

Product disposal: Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

14. Transport information

Road transport CN_DG:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Notice For Transportation: Transport according to local and national regulations. Ensure

containers will not leak, collapse, or being damaged when transported. DO NOT transport with incompatible materials. Transportation vehicle should be equipped with right fire-fighting equipment in case of emergency. Avoid solarization, drenched and high temperature when

transported.

15. Regulatory information

The following laws and regulations lay down provisions in terms of chemicals safety use, storage, transportation, loading/unloading, classification as well as symbol.

"Law of the People's Republic of China on Work Safety" (Adopted by the 28th meeting of 9th NPC standing committee on 29th June 2002, revised by 10th meeting of 12nd NPC standing committee on 31st Aug 2014).

Law of the People's Republic of China on the Prevention and Treatment of Occupational Diseases" (Adopted by the 24th meeting of 9th NPC standing committee on 27th October 2001, revised by 7th meeting of 13rd NPC standing committee on 29th Dec 2018).

"Law of the People's Republic of China on environmental protection" (Adopted by 11st meeting of 7th NPC standing committee on 26th December 1989, revised by 8th meeting of 12nd NPC standing committee on 24th Apr 2014).

"Regulation on the Safety Management of Hazardous Chemicals" (Adopted by 32nd State Council executive meeting on 4th December 2013).

"Regulations on License to Work Safety" (Adopted by 54th State Council executive meeting on 29th July 2014).

16. Other information

Issue date: 26.03.2022

Issue department: Product Safety & Regulatory Affairs for China

SDS No.: 120485 V001.6

TECHNOMELT PA 2035 BLACK known as REAMMIDE PAS 5035 S

Disclaimer:

This Safety Data Sheet has been generated in accordance with Chinese law only. It provides information on the chemical product in the aspects of safety, health, environment, etc, recommending preventive and protective measures and countermeasures in case of emergency. The information contained herein does not constitute a guarantee concerning the properties of the material. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties. The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Others:

The full text of all abbreviations indicated by codes in this safety data sheet section 3 are as follows:

H402 Harmful to aquatic life.