HIVIDEO

Model NO.	HI-66M				
SPECIFICATION	◆H.265 codec, high compression rate, ultra-low bit rate. ◆ Built-in IR LED, and the max. illumination distance is 30 m. ◆ ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. ◆ Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. ◆Intelligent monitoring: Intrusion, tripwire. ◆Abnormality detection: Motion detection, privacy masking, network disconnection, IP conflict, illegal access, and voltage detection. ◆ 12V DC/PoE power supply. ◆IP66 protection				
Camera					
Image Sensor	1/3"High-resolution CMOS Sensor	1/3"High-resolution CMOS Sensor	1/1.8"High-resolution CMOS Sensor	1/2.9"High-resolution CMOS Sensor	1/2.5"High-resolution CMOS Sensor
Resolution	3MP	5MP	5MP	6MP	8MP
Effective Pixels	5MP(2880*1616)	5MP(2880*1616)	5MP(2880*1616)	6MP(3200*1800)	4K(3840*2160)
Compression	H.264/H.265/H.265+				
TV System	PAL/NTSC				
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec				
S/N Ratio	≥52dB				
Scanning System	Progressive				
Video Output	Network				
Reset Button	NO				
LENS Type					
Lens Type	Fixed				
Lens	3.6mmF1.3 (2.8mm Select）	3.6mmF1.3 (2.8mm Select）	3.6mm / F1.0	3.6mmF1.3 (2.8mm Select）	3.6mm / F1.3
Night Vision					
Infrared LED	3PCS double Chip LED, White light, infrared can be selected				
Infrared Distance	25-30M				
IR Status	Under 5 Lux By Camera Sensor				
IR Power On	Sensor Auto Control				

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	ONVIF，P2P，CGI，HTTP，TCP/IP，IPv4，RTSP，UDP，NTP，DHCP，DNS，IP Filter
ONVIF	Support ONVIF
P2P	YES, Support QR Code
POE	Support 48-52V
Video Delay	0.3S (Within the Lan)
Main Stream 3	5MP@30fps (60HZ),5MP@25fps (50HZ)
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera	
Day/Night	Color/ B&W (IR-CUT) Smart
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	Support
ROI	/
Defog Mode	Support
BLC	Support
HDR	/
DWDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/VMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands, Czech
Interface	
Audio	Optional Audio in(Built-in)
Alarm	/
SD Card Slot	NO
RS485	/
General	
Housing	Metal+ Plastic , IP66
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-30℃ ~ +60℃ RH95% Max

Storage Temperature	-30℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 500mA POE 48-52V
Dimension	Size: 175(W) x 68(H) x 65(D)mm
Weight	Weight: 0.2Kg

www.hivideocctv.com